



بروفين للتجارة العامة (ش.ذ.م.م.)
PROFEN GENERAL TRADING L.L.C
PROFESSIONAL ENGINEERS

MARINE - INDUSTRIAL - VENTILATION - MACHINERY EQUIPMENTS & SPARES

Tel: +971 4 2289927, Fax: +971 4 2289947, P.O. Box: 181926
E-mail: Sales@profenuae.com Website: www.profenuae.com



VERISAFE®
Industrial encapsulation system

THE WORLDWIDE REFERENCE
FOR THERMOPLASTIC FILM





VERISAFE®

ULTRA RESISTANT THERMOPLASTIC SYSTEM

USED IN ALL AREAS WHERE PROTECTION IS NEEDED

RESPECTS THE ENVIRONNEMENT

PROTECTS THE APPLICATORS AND THE APPLICATION

MASTERS THE QUALITY OF THE AIR

INTERIOR AND EXTERIOR APPLICATION

APPLICATION IN INDUSTRIAL ENVIRONMENT



VERISAFE



VERISAFE®

MAJOR FEATURES

BI-DIRECTIONAL 60/45 % SHRINK
VERY GOOD WELDING QUALITY
PUNCTURE RESISTANCE
UV RESISTANCE
CERTIFICATION FOR FIRE RESISTANCE





VERISAFE®

APPLICATION PROCESS ON SCAFFOLDING OR CABLES

The welding and the shrinkage are essential parameters for the performance of the film on site.

The bi-directional shrink is reliable in time and gives the film a wind resistance at 110 miles/h.





VERISAFE®

APPLICATIONS AND PICTURES ON SCAFFOLDING





VERISAFE®

APPLICATIONS AND PICTURES IN TRANSPORT





VERISAFE®

CERTIFICATIONS & QUALITY

OUR FILMS HAVE FIRE RESISTANT CERTIFICATIONS :

LPS 1207 & 1215

EN 13501-1 - b, s1, d0 – M1

ISO 9001-2008 ANUAL QUALITY AUDIT





VERISAFE®

OUR RANGE OF FILMS

Name	Classification	Colour	Thickness
VERISAFE® ECO	LPS - M1 - EN 13501-1b-S1-d0	Transparent, white	250-280µ
VERISAFE® FR	LPS - M1 - EN 13501-1b-S1-d0	White	320 µ
VERISAFE® FR	LPS - M1 - EN 13501-1b-S1-d0	White	280 µ
VERISAFE® FR	FR Fire Resistant	White	300 µ
VERISAFE® ST	ST non fire resistant	Transparent, white	300 µ
VERISAFE® ST	ST non fire resistant	Transparent, white	300 µ
VERISAFE® FR	LPS - M1 - EN 13501-1b-S1-d0	White	250 µ
VERISAFE® FR	LPS - M1 - EN 13501-1b-S1-d0	White	200 µ
VERISAFE® FR	LPS - M1 - EN 13501-1b-S1-d0	White	200 µ
VERISAFE® FR	LPS - M1 - EN 13501-1b-S1-d0	White	265 µ
VERISAFE® ST	ST non fire resistant	White	190 µ

All those materials can be delivered from stock
Other qualities or colours can be produced (lead time 3-4 weeks)

